

Differential detector

Publication number: CN1267986 (A)

Publication date: 2000-09-27

Inventor(s): TENILER ANDRY M [US] +

Applicant(s): LUCENT TECHNOLOGIES INC [US] +

Classification:

- international: H04L25/03; H04L27/22; H04L25/03; H04L27/22; (IPC1-7): H04L27/22

- European: H04L25/03B6

Application number: CN20001003646 20000229

Priority number(s): US19990259949 19990301

Also published as:

EP1039706 (A1)
KR20000076753 (A)
JP2000253083 (A)
CA2298325 (A)
BR0000915 (A)


more >>

Abstract not available for CN 1267986 (A)

Abstract of corresponding document: EP 1039706 (A1)

The present invention provides a device and method for a receiver that iteratively detects and decodes differentially modulated symbols at a relatively lower error rate. The method and device of the present invention calculates extrinsic and a priori information and uses such information to more accurately detect and decode information carried by the symbols. First, a block of samples representing at least one symbol is received. Reliability information (or soft outputs) is calculated from the received at least one block of samples and any available a priori information.

Extrinsic information and updated a priori information are obtained from the calculated reliability information and such a priori information and extrinsic information are iteratively used to recalculate the reliability information. The iteratively calculated reliability information is ultimately used to decode information carried by the at least one block of samples.



Data supplied from the **espacenet** database — Worldwide